



AB360

6" Fire Bell For Indoor Use, 24Vdc

General

The AB360 is a 150 mm (6 inch) internal bell designed as an acoustic fire annunciator. Thanks to its small dimensions and overall design, it is ideal for in-door installation. The AB360 uses a 24 VDC supply and with the advantage of having very low current consumption, makes them compatible with most fire alarm systems on the market.

Applications

The AB360 is ideal for installing on any site, but are specifically good for installing on sites where a great number of bells are required. Because of the low current consumption, excessive power supplies can be avoided.

Construction

Designed for ease of installation, the AB360 features a robust steel gong. This ensures the reliable generation, of the universally recognizable fire alarm bell sound.



Details

- Suitable for indoor use
- Slim profile
- Low current consumption - 20mA
- Quick and easy installation
- Diode polarised
- Low maintenance
- Very reliable
- EN54-3 Approved
- CPD compliant

AB360

6" Fire Bell For Indoor Use, 24Vdc

Technical specifications

Electrical

Operating voltage	19 to 28 VDC
Current consumption	20 mA

Physical

Net weight	920 g
Colour	Red

Environmental

Environment	Indoor
IP rating	IP21C
Temperature Range	-10 to +55 °C

Standards & regulation

Certification	EN54-3
---------------	--------

Physical Characteristics

Sound Output	95 dB(A)
Diameter	6" (150 mm)
Gong construction	Steel

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 22 November 2019 - 20:02



**United
Technologies**

Climate | Controls | Security