

AS272

Indoor siren, 2 tones - without flash

The AS270 series of sirens is ideal for use as an internal alarm sounder for residential and industrial alarm applications.



Details

- Low current consumption
- 2 tones
- Pry-off & opening tamper protection
- Easy to install (1 fixing screw for cover)
- Vertical or horizontal mounting
- Self activating version available
- ANPI, NFA2P and VdS version available

AS272

Indoor siren, 2 tones - without flash

Technical specifications

General

| | |
|--------------------------------|-------------------------|
| Accessory group | Siren |
| Type | Indoor siren |
| Sounder output (dB @ distance) | 101 dB at 1 m (typical) |

Electrical

| | |
|---------------------|----------------------------|
| Power supply value | 10.0 to 14.2 VDC |
| Operating voltage | 10 to 14.2 V |
| Current consumption | 120 mA at 12 VDC (typical) |
| Battery capacity | 280 mAh, 10.8 V NiCd |

Physical

| | |
|---------------------|-------------------|
| Physical dimensions | 155 x 114 x 44 mm |
| Net weight | 220 g |
| Colour | White |
| Material | ABS |

Environmental

| | |
|-----------------------|--------------|
| Operating temperature | -25 to +55°C |
| IP rating | IP315 |

Regulatory

| | |
|---------------|----|
| Certification | CE |
|---------------|----|



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 9:31