

AS374

Fire Sounder, Hazardous Area, Multi Tone, Horn

General

The AS374 is a hazardous area electronic sounder for use in hazardous areas, to provide an audible warning signal in case of fire. It carries EExd IIC T4 rating, and has a marine grade aluminium housing with IP67 rating.

Hazardous Area

The AS374 is ATEX approved with ExII 2G and EExd IIC T4 ratings. It is housed in marine grade aluminium, and offers IP67 ingress protection.

Efficient and versatile

The AS374 provide a high sound output level, which ensures that it can be used indoor and outdoor. The AS374 sounder is supplied with a volume control as standard, allowing final audio adjustments to be made during installation. This allows of the output level to be reduced, when the sounder is used indoors.

With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation. A second and third tone, is available if extra wires are installed in the sounder circuit.



Details

- ATEX approved
- EExd IIC T4 rating
- 32 Tones user selectable
- 2nd and 3rd stage alarm
- IP67
- High output

AS374

Fire Sounder, Hazardous Area, Multi Tone, Horn

Technical specifications

Physical

Net weight	3.4 kg
Colour	Red

Environmental

Operating temperature	-50 to +55°C
Environment	Exd, Indoor, Outdoor
IP rating	IP67

Standards & regulation

Certification	CENELEC/ATEX
---------------	--------------

Operation

Continuous

Supply voltage

24 VDC

Current consumption

(see tone table in manual) 250mA typical

Sound output @ 1 metre

(see tone table in manual) up to 117dB(A)

Number of tones

32

Housing

Marine grade LM6 aluminium

Ingress protection

IP67

Operating temperature

-50°C to +55°C

Dimensions (Ø x D)

181 x 262 mm

Weight

3.4 Kg

Color

Red

